

N94-18554


AN ALGEBRAIC TURBULENCE MODEL  
FOR TURBOMACHINERY

by

Rodrick V. Chima  
NASA Lewis Research Center  
Cleveland, Ohio

## OVERVIEW

- MOTIVATION - TURBINE ENDWALL HEAT TRANSFER
- DESCRIPTION OF NEW MODEL
- RESULTS
  1. FLAT PLATE
  2. ANNULAR TURBINE CASCADE
  3. TURBINE ENDWALL HEAT TRANSFER
  4. SUPERSONIC COMPRESSOR BLADE
- SUMMARY



EXPERIMENTAL ENDWALL STANTON NUMBER CONTOURS

AS A FUNCTION OF  $\delta_{inlet}$  AND  $Re_{chord}$

# RVC3D (ROTOR VISCOUS CODE 3-D)


BY R. V. CHIMA

## DESCRIPTION


- EULER OR NAVIER-STOKES ANALYSIS  
FOR STEADY 3-D FLOWS IN TURBOMACHINERY

## FEATURES

- CARTESIAN FORMULATION, ROTATION ABOUT X-AXIS  
RECTANGULAR OR ANNULAR GEOMETRIES
- SOLVES NAVIER-STOKES EQUATIONS  
THIN-LAYER FORMULATION, (NO STREAMWISE VISCOUS TERMS)  
RETAINS HUB-TO-TIP & BLADE-TO-BLADE VISCOUS TERMS  
BALDWIN-LOMAX OR CEBECI-SMITH TURBULENCE MODEL  
SIMPLE TIP CLEARANCE MODEL
- NODE-CENTERED FINITE-DIFFERENCE FORMULATION  
EXPLICIT 4-STAGE RUNGE-KUTTA TIME-MARCHING SCHEME  
2ND + 4TH ORDER ARTIFICIAL VISCOSITY, EIGENVALUE SCALING  
VARIABLE  $\Delta t_{i,j}$  & IMPLICIT RESIDUAL SMOOTHING  
HIGHLY VECTORIZED & AUTOTASKED FOR CRAY Y-MP
- STACKED C-TYPE GRIDS



## TURBULENT VISCOSITY PROFILE



## CEBECI-SMITH & BALDWIN-LOMAX MODELS

### INNER LAYER: PRANDTL-VAN DRIEST FORMULATION

#### CEBECI-SMITH

$$\mu_i = \rho l^2 |\partial u / \partial y|$$

$$l = \kappa y D$$

$$D = 1 - \exp(-y^+ / A^+) \quad \text{VAN DRIEST DAMPING}$$

#### BALDWIN-LOMAX

$$\mu_i = \rho l^2 |\omega|$$

### OUTER LAYER: CLAUSER FORMULATION

#### CEBECI-SMITH

$$\mu_o = K \rho \gamma \delta^* u_e$$

$$\gamma = \left[ 1 + 5.5 \left( \frac{y}{\delta} \right)^6 \right]^{-1} \quad \text{KLEBANOFF INTERMITTENCY FUNCTION}$$

#### BALDWIN-LOMAX


$$\mu_o = K \rho \gamma C_{cp} \min \begin{cases} y_{maz} f_{maz} \\ \text{wake option} \end{cases}$$

$$f(y) = y |\omega| D$$


# BALDWIN-LOMAX MODEL ANALYSIS

(SEE PAPER FOR DETAILS)


1. ASSUME SUBLAYER-WALL-WAKE VELOCITY PROFILE
2. CALCULATE BALDWIN-LOMAX FUNCTION  $f(y)$   
 MAX. OCCURS AT  $y_{max} = .646\delta$   
 INDEPENDENT OF PRESURE GRADIENT  
 NO MAX. FOR INFINITELY FAVORABLE  $\partial p/\partial x$
3. SPURIOUS MAX. CAN OCCUR AT EDGE OF VISCOUS SUBLAYER  
 MOST LIKELY AT LOW Re & FAVORABLE  $\partial p/\partial x$



1. VELOCITY PROFILES,  $Re_s = 105,000$



2. B-L FUNCTION  $f(y)$



3. SPURIOUS MAXIMUM IN  $f(y)$

## PROPOSED TURBULENCE MODEL

INNER LAYER (SIMILAR TO BALDWIN-LOMAX)

$$\begin{aligned}\mu_i &= \rho l^2 |\omega| \\ l &= \kappa y D \\ D &= 1 - \exp(-y^+/A^+) \\ y^+ &= y \frac{u^*}{\nu} \\ u^* &= \sqrt{\frac{\tau_{wall}}{\rho}}\end{aligned}$$

## PROPOSED TURBULENCE MODEL

### PRESSURE GRADIENT EFFECTS

- ACCELERATING FLOWS TEND TO RELAMINARIZE
- MODELLED BY INCREASING  $A^+$  IN FAVORABLE  $\partial p / \partial s$
- CEBECI'S EXPRESSION FOR  $A^+$  USED:

$$A^+ = \frac{26}{\sqrt{1 + 11.8 p^+}}$$

$$p^+ = \frac{\nu}{\rho u_*^3} \frac{\partial p}{\partial s}$$

- PRESSURE GRADIENT EVALUATED USING:

$$\frac{\partial p}{\partial s} \approx \frac{\vec{V}_e}{|\vec{V}_e|} \cdot \nabla p$$

- "EDGE VELOCITY"  $\vec{V}_e$  EVALUATED AT A GRID LINE FAR ENOUGH FROM THE WALL TO GIVE THE GENERAL FLOW DIRECTION
- KAYS-MOFFATT EXPRESSION WAS TESTED, EFFECTS TOO STRONG

## PROPOSED TURBULENCE MODEL

### LOCAL SHEAR MODEL

- IN STRONGLY ACCELERATING FLOWS  $\tau^+$  DECREASES WITH  $y^+$
- MODELLED BY REPLACING  $\tau_{wall}$  WITH  $\tau(y)$  IN  $D$

$$D = 1 - \exp(-y^+ / A^+)$$

$$y^+ = y \sqrt{\frac{\rho (\mu_l + \mu_t)}{\mu_l} |\omega|}$$

- ERROR IN ORIGINAL PAPER - USED  $\mu_l |\omega|$  ONLY
- USED BY KAYS, PATANKAR-SPALDING, OTHERS
- ALSO USED TO AVOID PROBLEMS AT SEPARATION WHEN  $\tau_{wall} \rightarrow 0$

## PROPOSED TURBULENCE MODEL

### OUTER LAYER

$$\begin{aligned}\mu_o &= K \rho \gamma \min \left\{ \frac{F}{C_{wk} \bar{y} (|V_{max}| - |V_{min}|)} \right. \\ \gamma &= \left[ 1 + 5.5 \left( \frac{C_{Kleb} y}{\bar{y}} \right)^6 \right]^{-1} \\ C_{wk} &= 0.825 \\ C_{Kleb} &= 0.55\end{aligned}$$

## PROPOSED TURBULENCE MODEL


### OUTER LAYER - FUNCTION F

- DEFINE  $F = \int f dy$
- INTEGRATE BY PARTS ASSUMING  $|\omega| \rightarrow 0$  AS  $y \rightarrow \delta$

$$\begin{aligned}F &= \int_0^\infty y |\omega| dy \\ &\approx \int_0^\delta y \frac{\partial u}{\partial y} dy \\ &= uy \Big|_0^\delta - \int_0^\delta u dy \\ &= \int_0^\delta (u_e - u) dy \\ F &= \delta^* u_e\end{aligned}$$

- USE F DIRECTLY IN CEBECI-SMITH OUTER FORMULATION
- ELIMINATES CONSTANT  $C_p$
- DOES NOT REQUIRE KNOWLEDGE OF  $\delta$  OR  $u_e$
- DISCOVERED INDEPENDENTLY BY D. A. JOHNSON, AIAA 92-0026

# PROPOSED TURBULENCE MODEL



## OUTER LAYER - LENGTH SCALE $\bar{y}$

- $\bar{y}$  IS THE CENTROID OF THE  $f(y)$  CURVE

$$\int_0^{\bar{y}} f(y) dy = \int_{\bar{y}}^{\delta} f(y) dy$$

- EVALUATE USING COLE'S VELOCITY PROFILES

$\Pi$	$\bar{y}/\delta$
0	.5
.5	.55
$\infty$	.606

- USE EQUILIBRIUM VALUE  $C_{Kleb} = \bar{y}/\delta = .55$

# PROPOSED TURBULENCE MODEL

## OUTER LAYER - WAKE MODEL

$$\mu_o = K \rho \gamma \min \left\{ \frac{F}{C_{wk} \bar{y} (|V_{max}| - |V_{min}|)} \right\}$$

- LOWER OPTION IS A CONVENTIONAL WAKE MODEL
- EVALUATE  $C_{wk}$  BY EQUATING TWO OPTIONS, ASSUMING

$$\begin{aligned} \bar{y}_{sep} &= .606 \delta \\ F_{sep} &= u_e \delta / 2 \\ \Delta V / u_e &\approx 1 \end{aligned}$$

- GIVES  $C_{wk} = 0.825$



# PROPOSED TURBULENCE MODEL

## 3-D IMPLEMENTATION

- GRANVILLE BLENDING FUNCTION

$$\mu_{eff} = \mu_o \tanh \frac{\mu_i}{\mu_o}$$

- MODEL APPLIED INDEPENDENTLY IN BLADE-TO-BLADE ( $\eta$ ) AND SPANWISE ( $\zeta$ ) DIRECTIONS
- INNER LAYER - USE BULEEV LENGTH SCALE


$$y_i = \frac{2s_\eta s_\zeta}{s_\eta + s_\zeta + \sqrt{s_\eta^2 + s_\zeta^2}}$$

- OUTER LAYER - USE ACTUAL DISTANCE ACROSS PROFILE

$$y_o = s_\eta \text{ OR } s_\zeta$$



- BLEND  $\eta$  AND  $\zeta$  PROFILES VECTORALLY

$$\mu_{turb} = \sqrt{\mu_{i\eta}^2 + \mu_{i\zeta}^2}$$




COMPARISON OF FLAT PLATE VELOCITY PROFILES  
TO SPALDING'S COMPOSITE LAW OF THE WALL


GOLDMANS ANNULAR CASCADE  
 CONSTANT RADIUS HUB  
 97 x 31 x 33 GRID




COMPUTED & MEASURED PRESSURE DISTRIBUTIONS  
 FOR THE ANNULAR TURBINE CASCADE



COMPUTED & MEASURED LOSS COEFFICIENT PROFILES  
FOR THE ANNULAR TURBINE CASCADE




COMPUTED & MEASURED EFFICIENCY CONTOURS  
IN THE WAKE OF THE ANNULAR TURBINE CASCADE



TURBINE CASCADE


BOYLE'S LINEAR CASCADE  
STANTON NUMBER  $\times 1000$   
 $Re_c = 78,000$




COMPUTED

MEASURED


BOYLE'S LINEAR CASCADE  
 STANTON NUMBER  $\times 1000$   
 $Re_c = 490,000$



COMPUTED




MEASURED



# CONTOUR LEVELS

1.00000  
2.00000  
3.00000  
4.00000  
5.00000  
6.00000  
7.00000  
8.00000  
9.00000  
10.00000  
11.00000  
12.00000  
13.00000  
14.00000  
15.00000  
16.00000  
17.00000  
18.00000  
19.00000  
20.00000  
21.00000  
22.00000  
23.00000  
24.00000  
25.00000  
26.00000  
27.00000  
28.00000  
29.00000  
30.00000  
31.00000  
32.00000  
33.00000  
34.00000  
35.00000  
36.00000  
37.00000  
38.00000  
39.00000  
40.00000  
41.00000  
42.00000  
43.00000  
44.00000  
45.00000  
46.00000  
47.00000  
48.00000  
49.00000  
50.00000  
51.00000  
52.00000  
53.00000  
54.00000  
55.00000  
56.00000  
57.00000  
58.00000  
59.00000  
60.00000  
61.00000  
62.00000  
63.00000  
64.00000  
65.00000  
66.00000  
67.00000  
68.00000  
69.00000  
70.00000  
71.00000  
72.00000  
73.00000  
74.00000  
75.00000  
76.00000  
77.00000  
78.00000  
79.00000  
80.00000  
81.00000  
82.00000  
83.00000  
84.00000  
85.00000  
86.00000  
87.00000  
88.00000  
89.00000  
90.00000  
91.00000  
92.00000  
93.00000  
94.00000  
95.00000  
96.00000  
97.00000  
98.00000  
99.00000  
100.00000




ORIGINAL PAGE IS  
OF POOR QUALITY

# TURBULENT VISCOSITY NEW MODEL

# CONTOUR LEVELS

1.00000  
2.00000  
3.00000  
4.00000  
5.00000  
6.00000  
7.00000  
8.00000  
9.00000  
10.00000  
11.00000  
12.00000  
13.00000  
14.00000  
15.00000  
16.00000  
17.00000  
18.00000  
19.00000  
20.00000  
21.00000  
22.00000  
23.00000  
24.00000  
25.00000  
26.00000  
27.00000  
28.00000  
29.00000  
30.00000  
31.00000  
32.00000  
33.00000  
34.00000  
35.00000  
36.00000  
37.00000  
38.00000  
39.00000  
40.00000  
41.00000  
42.00000  
43.00000  
44.00000  
45.00000  
46.00000  
47.00000  
48.00000  
49.00000  
50.00000  
51.00000  
52.00000  
53.00000  
54.00000  
55.00000  
56.00000  
57.00000  
58.00000  
59.00000  
60.00000  
61.00000  
62.00000  
63.00000  
64.00000  
65.00000  
66.00000  
67.00000  
68.00000  
69.00000  
70.00000  
71.00000  
72.00000  
73.00000  
74.00000  
75.00000  
76.00000  
77.00000  
78.00000  
79.00000  
80.00000  
81.00000  
82.00000  
83.00000  
84.00000  
85.00000  
86.00000  
87.00000  
88.00000  
89.00000  
90.00000  
91.00000  
92.00000  
93.00000  
94.00000  
95.00000  
96.00000  
97.00000  
98.00000  
99.00000  
100.00000



## SUMMARY

- SPURIOUS MAXIMUM IN B-L FUNCTION  $f(y)$  CAN GIVE INCORRECT TURBULENT LENGTH SCALE & ERRATIC  $St$  OR  $C_f$  PATTERNS
  - MOST LIKELY AT LOW  $Re$  AND FAVORABLE  $\partial p/\partial s$
- NEW TURBULENCE MODEL PROPOSED
  - INTEGRAL RELATIONS FOR  $\delta^+ u_e$  AND  $\delta$  USED WITH C-S MODEL
  - EFFECTS OF  $\partial p/\partial s$  MODELED
  - WAKE MODEL PROPOSED
- FLAT PLATE
  - B-L & NEW MODEL AGREE WITH LAW OF THE WALL
  - LOCAL SHEAR MOD. DOES NOT AGREE WITH LAW OF THE WALL
- ANNULAR TURBINE
  - GOOD AGREEMENT WITH EXPT. PRESSURE DISTRIBUTION
  - WAKE MIXING UNDER-PREDICTED
- TURBINE ENDWALL HEAT TRANSFER
  - VARIATIONS IN ENDWALL  $St$  WITH  $Re$  PREDICTED WELL
  - EFFECTS OF  $\partial p/\partial s$  IMPORTANT
- TRANSONIC FAN
  - SHEAR LAYER FROM BOW SHOCK ACTS LIKE VISCOUS LAYER
  - NEW MODEL OVERPREDICTS L.E.  $\mu_t$
  - B-L MODEL PREDICTS REASONABLE L.E.  $\mu_t$